



VS 204 OILLESS



Cylinders				
Cilindri	2			
Bore				
Alesaggio	2,17	in	55	mm
Stroke				
Corsa	1,18	in	30	mm
Displacement				
Cilindrata	8,70	cu.in.	142,5	cm ³
Rated speed				
Velocità di rotazione	1450	rpm	1450	min-1
Max. working pressure				
Pressione massima	116	psi	8	bar
Air displacement				
Aria aspirata	7,3	cfm	207	l/min
Oil quantity				
Quantità olio	0,000	gal	0,00	lt
		ozs	0,00	kg

		psi	20	cfm	6,6		bar	1,4	l/min	186
		psi	40	cfm	6,4		bar	2,8	l/min	180
F.A.D.	AT	psi	70	cfm	5,5	ARIA RESA A	bar	4,8	l/min	155
(FREE AIR DELIVERY)		psi	90	cfm	5,1		bar	6,2	l/min	144
		psi	100	cfm	4,8		bar	6,9	l/min	136
		psi	116	cfm	4,45		bar	8,0	l/min	126

Motor power / Potenza motore	2	CV
Input power / Potenza assorbita	2,1	kW
Power supply / Alimentazione	230 V / 50 Hz / 1 ~	
	400 V / 50 Hz / 3 ~	

Rated supply / Assorbimento	10 A @ 230 V / 50 Hz / 1 ~
	6 A @ 400 V / 50 Hz / 3 ~

Capacitor / Condensatore	230 V / 50 Hz / 1 ~	30 µf	450 V
---------------------------------------	---------------------	-------	-------

Insulation class / Classe di isolamento	F
--	---

Weight / Peso	55,1 lbs	25 Kg
----------------------------	----------	-------

Dimensions / Dimensioni	16,5 in / 420 mm	L
	11,0 in / 280 mm	P
	12,6 in / 320 mm	H

THERMAL PROTECTION WITH MANUAL RESET
PROTEZIONE TERMICA A RIPRISTINO MANUALE